

HOLLYWOOD MOTORSPORTS LLC 1/2 ton stock truck class 2017

VEHICLE PREPARATION TRUCK RULES FOR CERTIAN COUNTY FAIRS BUT NOT THE SAINT CROUX FALLS COUNTY FAIR CHECK YOUR SCHUEDLE OF EVENTS ON MY WEBSITE

THIS IS A SUPER STOCK BUILD DONT LIKE IT WE HAVE A SLIGHTLY HEAVIER BUILD TRUCK CLASS

Full-face helmets with chin guard mandatory

Remove all glass, chrome, plastic, moldings, headliner, flammable material, A/C coolant, antifreeze, trailer hitches and interior decorating
Stock gas tank must be removed. A small metal tank must be mounted in the rear Seat area. The tank must be very secure and covered. Use proper rated fuel lines, Plastic tanks must be in a metal box. NO EXCEPTIONS
Electric fuel pump allowed but switch must be clearly marked on/off.
Floor shifter allowed. Ignition and wiring modifications (hotwire) allowed.
Hood must have 12" x 12" minimum hole to easily extinguish fires. Extra hole(s) in hood not required if header holes are least 12" x 12".

TRUCKS

1/2 TON ONLY 4 wheel and 2 wheel trucks and suburbans allowed. 4 wheel drive vehicles must Remove front drive shaft. Must be a pickup truck frame standard cab standard box no exceptions all cabs must match frame **year *make. Max height 26 inches Minimum frame height is 19
ALL FRAMES MUST BE PICKUP TRUCK **NO BODY LIFTS OR SUSPENTION LIFTS OR SUBERBAN STYLE NO FLATT BED, OR ANY OTHER STYLE FRAMES

BUMPERS

You may change front bumper to a 80 AND NEWER car type, stock truck bumper OR tube or pipe in a straight contour may be used.

3 x 6 max. All bumpers must be hollow 3/8 max thick on tube no stuffed bumpers.

May be bolted on with a factory truck bracket. Or you may weld

The bumper to the frame. Nothing welded past 4 inches from the front of the

Frame. NO EXCEPTIONS You may weld a 5x5 plater to the front of the frame to bolt your bumper to.

You may run up to 3x6 tube or pipe for a bumper STRAIGHT CONTOUR 3/8 max thickness must be hollow 3/8 max thick.

ALL TYPE BUMPERS MUST BE HOLLOW MUST BE ABLE TO SEE INSIDE

HOOD

Six bolts or six chains or six wires will be allowed 1 inch max . Two may go to frame, the

Other four may be sheet metal to sheet metal. If you choose to use threaded rod it

must be welded vertically stock core support along with stock position. , one inch max. Must be within 4 inches of stock

location. Only one of these three may be used.

STEERING

NO WELDING OR STRENGTHING tie rods, must be a stock tie rod. Aftermarket steering Colum allowed.

ENGINE

Motors may interchange, must be within 4 inches of factory location.

NO distributor protectors, trans brace, LOWER CRADLE ALLOWED WITH STOCK LOWER FRAME MOUNTS.

TRANS

no trans brace whatsoever. you may have a trans cooler but cannot strengthen truck.

any driveshaft allowed. Slider driveshaft allowed

RADIATORS

Must be in stock location. No homemade radiators. No Radiator protectors allowed,

Aftermarket radiators allowed. You may bolt air conditioner condenser in front of radiator.

DRIVER'S SAFETY

UNLIMITED DRIVERS DOOR PROTECTION 3 INCHES PAST SEAMS .

One bar in the dash is allowed. One bar behind the seat is allowed. If you choose

you may connect these along the inside of door. Strongly recommended, two

down bars off back seat bar to the frame, vertical only. Extended cabs and crew cabs*** All cage components from 3 inches from the back side of drivers seat must be free floating. You may weld box to cab outside only. Dash bar must be 6 inches from trans hump. No down legs to frame from 6 inches of the back of your seat in cab area must float, extended cabs will be closely watched.
5X5 MAX SIZE ON TUBE OR PIPE NO BIGGER NO SMALLER than 2 inch tube or pipe
ROLL OVER BAR CONSISTS OF 2 UPRIGHTS AND 1 HORIZONTAL BAR OVER CAB ONLY. NO FORWARD OR REARWARD BARS.

DOORS

Doors may be chained, wired, or welded solid max 1/4"x3" inch wide strap. Nothing welded to frame.

FUEL

no alcohol motors

Fuel cell is highly recommended in a steel box. This is to be located in the most forward center of box or inside of cab. Gas line to be run in a protective conduit.

TIRES .

No ply

Restriction,. Must be rubber AIR FILLED tires

Nothing higher than 33 inches tall. NO tire protectors ,no bead locks. valve stem protectors allowed.

SUSPENSION

Stock springs ,You may clamp springs, 6 per side. Clamp size, 7/16 bolts, 3/8 max thick, 3 inch

wide material. Max height 26 inches. Minimum frame height is 20 inches

. No homemade springs. NO LEAF CONVERSION ON 1989 AND NEWER GM OR FORD TRUCKS UNLESS THEY CAME FACTORY HOLES FOR LEAF PERCH MOUNTS. NO IF ANDS OR BUTS.

BATTERIES

Two max, must be covered or in a box.

All battery boxes and fuel cells must be Mounted.

BODY BOLTS AND BOX

Body bolts 3/4" max, 6"x 6" washers in stock mount locations. You may add 4 extra body bolts in the box and 2 in the cab, they may be up to 3/4 bolt welded only vertical to the frame . Box must remain upright in stock location, NO tucking NO SHORTING OF THE BOX. you may have a slightly larger plate bigger than your fuel cell to sit on in box for safty. fuel cell plate no larger the 3 inches bigger then fuel cell must be free floating bolted to sheet metal only. Not attached to back seat bar or cab. **All boxes that tucked themselves in the act of derbing need to be straightened out in respectable manner if they run the next event.**

TAILGATE

Tailgate must remain upright in stock location. You have three ways of fastening your tailgate. You may wire or chain 2 per seam or weld a 3 inch wide strap per seam. Outside only.

TAILGATE MAY BE DROPPED DOWN A MAX OF 8 INCHES BUT MUST BE VERTICAL

you may weld tailgate to frame or bumper. no tucking

REARENDS

NO 8 BOLT REARENDS PERIOD 5 OR 6 BOLT ONLY , DONT CARE DONT CALL IF IT HAD ONE IN IT.

One 3/8 chain per side to hold rear end in NO BRACED REAR ENDS, NO AFTERMARKET AXLES

WELDING" REPAIR

on a bent area must be clearly bent not stress marks you get up to 3x12 by 1/4 per frame rail when its gone its gone this does not mean 13inches. NO PLATED FRESH TRUCKS

THIS IS A STOCK TRUCK CLASS Height restriction will be CLOSELY MONITORED, BOTTOM OF FRAME TO GROUND questions call 9204102008

