

# **HOLLYWOOD MOTORSPORTS**

## **DEMOLITION DERBY ENTERTAINMENT, LLC 2017**

*Demolition Derby Rules for multipal minies (s10s,minie vans,small suvs,etc)  
2015 drive for 5, county fairs, charity*

### VEHICLE PREPARATION

MANTITORY FULL FACE HELMETS WITH CHIN GUARD

NO CHRYSLER V BUMPERS

Remove all glass, chrome, plastic, moldings, headliner, flammable material, A/C coolant, antifreeze, trailer hitches and interior decorating

Stock gas tank must be removed. A small metal tank must be mounted in the rear Seat area. The tank must be very secure and covered. Use proper rated fuel lines, Plastic tanks must be in a metal box. **NO EXCEPTIONS**

Electric fuel pump allowed but switch must be clearly marked on/off.

No more than (2) batteries allowed which must be relocated to front passenger Floor, secured and covered.

Floor shifter allowed. Ignition and wiring modifications (hotwire) allowed.

Hood must have 12" x 12" minimum hole to easily extinguish fires. Extra hole(s) in hood not required if header holes are least 12" x 12".

Car and driver qualify as a team for the feature.

**1. 4 wheel and 2 wheel trucks and suv allowed. 4 wheel drive vehicles must remove one drive shaft.**

#### **BUMPERS**

**1. You may change front bumper to a car type, tube or pipe may be used. 3 x 4 May be bolted on with a factory automotive or truck bracket. Or you may weld to the bumper to the frame. Nothing welded past 4 inches from the front of the frame. NO EXCEPTIONS**

#### **HOOD**

**1. Six bolts or six chains or six wires will be allowed. Two may go to frame, the other four may be sheet metal to sheet metal. If you choose to use threaded rod it must be welded vertically, one inch max. Must be within stock location. Only one of these three may be used.**

#### **ENGINE**

**1. Motors may interchange, must be within 4 inches of factory location. Distributor protectors are not allowed tranmission braces not allowed NO ENGINE CRADLES**

#### **RADIATORS**

**1. Must be in stock location. No homemade radiators. Radiator protectors allowed but no wider than radiator. Mesh or expanded metal type material, 1/4" max. Four 3/8 bolts to fasten max. No welding. No radi barrels**

#### **DRIVER'S SAFETY**

1. One bar in the dash is allowed. One bar behind the seat is allowed. If you choose you may connect these along the inside of door. Strongly recommended, two down bars off back seat bar to the frame, vertical only. You may weld box to cab outside only two 8 inch straps per side. Minie vans please weld your large doors if able. Dash bar must be 6 inches from trans hump.

#### **DOORS**

1. Doors may be chained, wired 2 spots per seam, or welded 5 on 5 off max 1/4"x3" inch wide Strap. Nothing welded to frame. . Minie vans please weld your large doors if able.

#### **FUEL**

1. Fuel cell is highly recommended in a steel box. This is to be located in the most Forward center of box or inside of cab. Gas line to be run in a protective conduit.

#### **TIRES**

1. No ply restriction. . Nothing higher than 30 inches tall.

#### **SUSPENSION**

1. You may clamp springs, 4 per side. Clamp size, 7/16 bolts, 3/8 max thick, 5 inch Length material. Max height 20 inches. Minimum frame height is 16 inches. No Homemade springs.

#### **BATTERIES**

1. Two max, must be covered or in a box. All battery boxes and fuel cells must be Mounted.

#### **BODY BOLTS AND BOX**

1. Body bolts 3/4" max, 6"x 6" washers in stock mount locations. You may add 4 extra body bolts in the box and 2 in the cab on pickups only , they may be up to 3/4 bolt welded only vertical to the frame . Box must remain upright in stock location, no tucking.

#### **TAILGATE**

1. Tailgate must remain upright in stock location. You have three ways of fastening your tailgate. You may wire or chain or weld a 3 inch wide strap per seam. Out side only

#### **AXELS**

- Stock type rear-ends for that size and type of vehicles. Swapping rear ends is ok as long as it's a small truck or SUV type. ( No full size truck rear ends) You may chain your rear to frame one 3/8 chain per side.

#### **FRAME\***

Repairs only allowed on a kinked area {not stressed}  
8 inches by 3 inches by 1/4 total per frame rail when its gone to bad.

#### **WELDING**

Nothing may be welded unless stated in the rules. This is your warning! Otherwise Prepare to stay on your trailer small repairs must call.

## **SPIRIT OF THE RULE**

**Although every effort has been directed  
toward complete  
Understandable and correct rules as well as  
the same factors in  
Putting them into print, Hollywood  
Motorsports cannot possible  
Anticipate every situation, circumstance or  
interpretation.**

**With this in mind we must refer to the spirit  
of the rule.**

**ANY QUESTIONS CALL 9204102008**